

Continental 
The Future in Motion



TeleMaster™
A solid building solution

TeleMaster™

A solid building solution

Telehandlers are used in a variety of environments such as commercial and residential construction and agricultural sites. Telehandlers have multiple attachments including buckets, pallet forks, and winches. With the ability to lift to extreme heights, Telehandlers call for a tyre with high load capacity and outstanding stability.

The TeleMaster™. A solid solution for all terrains.

The TeleMaster™ is a solid OTR tyre that was developed for the specific demands of Telehandler users. The tyre construction of the TeleMaster™ is made up of different highly specialised rubber compounds each fulfilling a different task. The inner layer compound combines damping properties with low rolling resistance values. This results in a comfortable ride and low heat build-up so longer travel distances of the machine are possible. The tread compound, wrapped bead to bead, ensures sidewall protection and is optimised in terms of cut resistance and wear behaviour to ensure longevity. This in its entirety results in the lowest total cost of ownership. The non-directional tread pattern design combines traction and comfort. A distinctive centre rib supports a comfortable driving experience, especially on hard surfaces. The massive tread blocks with many gripping edges ensure traction and self-cleaning on looser ground conditions like mud and gravel sites.

The TeleMaster™ is a solid, flat-proof solution that removes the need to check inflation pressure, or fill with polyurethane, and still provides lasting stability and comfort.



Outstanding service life and high comfort

The advanced solid three layer construction delivers a comfortable ride and offers a long service life.



High damage protection

The reinforced sidewalls prevent punctures and cuts.



High traction

The circumferential rib tread pattern ensures high traction in both directions.

Tyre Size	Rim	Tyre Data				Load capacity kg (lbs)				LI/SS
		Diameter mm (inch)	Width mm (inch)	Tread depth mm (32")	Weight kg (lbs)	6 km/h (3.7 mph)	10 km/h (6.2 mph)	25 km/h (15.5 mph)	Static load kg (lbs)	
315/95-28 /8.50	8.5-28	1283 (50.51)	302 (11.89)	60 (76/32)	265 (584)	8.280 (18.254)	7.521 (16.580)	6.900 (15.211)	10.419 (22.970)	175 A6
360/85-28 /10.00	10.0-28	1330 (52.36)	340 (13.39)	65 (82/32)	336 (741)	10.500 (23.148)	9.538 (21.027)	8.750 (19.290)	13.213 (29.130)	183 A6